



**TELEDYNE
FLIR**

THERMAL VISION FOR RECREATIONAL BOATING



NIGHTTIME ON THE WATER MADE SAFER WITH FLIR

FLIR maritime thermal imaging systems turn night into day, keeping you safe and secure on the water and letting you boat with confidence.

SEE THE HEAT

Thermal imaging cameras detect and display images based on tiny differences in heat, not light. From pitch black, to moonlight, to severe midday glare, FLIR detectors capture the thermal energy emitted or reflected by everything, even ice. FLIR cameras then convert the small differences in temperature into easy-to-interpret infrared video images, allowing you to see at night and navigate in total darkness.



CONTENTS

- 4 The Thermal Advantage
- 8 Understanding Resolution and Range
- 10 Scion OTM Handheld Thermal Monocular
- 11 MD-Series Fixed Mount Thermal Cameras
- 13 M232 Marine Thermal Vision Cameras
- 15 M300 Marine Thermal Cameras with Gyro-Stabilization
- 20 M400 and M400XR Multi-Sensor Camera System
- 26 M500 Cooled Multi-Sensor Camera System
- 32 Features Comparison Chart
- 34 Specifications



FOR EVERYTHING FROM KAYAKS TO SUPER YACHTS, FLIR OFFERS CUTTING-EDGE MARINE THERMAL CAMERAS THAT ARE RUGGED, RELIABLE, AND SIMPLE TO USE.

THE THERMAL ADVANTAGE



BOAT SAFER AND AVOID DANGER



Day or night, FLIR thermal imaging detects obstacles, such as jetties, rocks, navigation aids, and more. Charged by daylight, these objects continue to emit infrared heat all night long.



Thermal imaging instantly detects kayaks, paddleboards, and personal watercraft. The kayaker's own body heat makes him a bright target for FLIR thermal imaging.



Color Thermal Vision™ (CTV) technology blends thermal and HD colour video for enhanced identification of buoys and other vessels.

ENHANCED SITUATIONAL AWARENESS



FLIR thermal imagers make it easy to confirm the positions of navigation aids and landmarks. Systems with pan/tilt/zoom (PTZ) gimbals can even integrate with select multifunction navigation displays and radar systems, making target ID even easier.

Thermal imaging instantly reveals other vessels masked by background lighting and solar glare. Because they see heat, rather than visible light, FLIR cameras deliver the same high-quality images day or night.


NAVIGATE SMARTER



Thermal imaging not only lets you see approaching vessels, but also the activities of those onboard. Many systems offer digital and optical zoom to further enhance small or distant objects.




SEE AT NIGHT



Your Vision: Floating debris is almost impossible to spot at night, especially with bright urban back lighting.



FLIR Vision: Thermal imaging easily detects the floating box, as well as the bridge span ahead. The thermal camera is completely immune to the effects of bright city lights and glare.



In addition to the power of thermal vision, many FLIR maritime cameras feature ClearCruise™ Object Detection technology for recognizing and highlighting non-water objects, such as boats, buoys, or floating debris.

YOUR VISION VERSUS FLIR VISION



Your Vision: Emergency lights on a police boat mask its navigation lights, making it hard to determine its aspect at night.



FLIR Vision: Thermal imaging is immune to visible light and glare. Not only can we clearly see the police boat, we can also see the buoy and jetty astern of it.

Thermal imaging works night and day, in total darkness or bright sunlight, through smoke, dust, and even light fog to keep your passengers and crew safe from hazards and threats.


FLIR - THE WORLD'S SIXTH SENSE



At FLIR, we develop a wide range of technologies that enhance perception and awareness. We bring innovative sensing solutions into daily life through our thermal imaging, visible-light imaging systems, location technologies, measurement and diagnostic products, and advanced threat detection systems. Our products improve the way people interact with the world around them, enhance public safety and well-being, increase energy efficiency, and enable healthy and entertained communities.

UNDERSTANDING RESOLUTION AND RANGE

FLIR offers a range of thermal imaging cameras with varying levels of image resolution. Much like a digital camera, FLIR cameras with higher pixel counts offer more detail, but more importantly, high-resolution thermal cameras see objects at greater distances. For example, an uncooled, 640-resolution FLIR camera can detect a vessel at almost twice the range of a 320-resolution camera. Premium cameras with enhanced optics and cooled thermal cores offer even longer-range target detection capabilities.



Lower Resolution



Thermal imagers with lower resolutions provide good basic target detection and identification at short to medium ranges.

Higher Resolution



The increased pixel density of high-resolution systems gives them increased contrast, more lifelike detail, and higher sensitivity at long range.

VISION IN TOTAL DARKNESS

Daylight cameras, image intensified night vision (I²), and the human eye all create images from reflected light. Traditional green night vision scopes and goggles all magnify small amounts of visible light. However, traditional imagers have the same limitations as the human eye. If there isn't enough light available, they don't work well. Plus, during daylight and twilight hours, they aren't useful either because there is too much light for them to work effectively.

FLIR thermal cameras work both day and night, regardless of light. They're totally immune to the effects of darkness, glare, or even direct sunlight.



Your Vision



The human eye can't react well to darkness pierced by bright lighting. The lights of the approaching vessel are blinding, making it impossible to see the details.

Traditional Gen3 Image Intensified Night Vision



Image intensified night vision scopes and goggles are also at a disadvantage. They over-magnify the lighting in the scene, hurting your eyes and concealing important details.

FLIR Thermal Image



Since the thermal camera sees heat, rather than light, it is immune to the blinding effects of the boat's navigation lights. We can clearly see two occupants in the approaching RIB.

FLIR SCION[®] OTM




HANDHELD THERMAL CAMERA

The FLIR Scion[®] OTM captures clear thermal imaging and leverages an easy-to-use interface to quickly detect objects of interest in complete darkness and through glaring light or haze. Scion records geotagged video and still images for playback long after the day is done. Operation is simple with intuitive on-screen graphics and a simple, single-handed control. A rugged, IP67-rated housing allows Scion to deliver reliable thermal imaging in the harshest weather and most demanding outdoor environments.









The high-resolution Boson™ core in FLIR Scion delivers detailed, high-contrast thermal images day or night.

SCION OTM THERMAL DETECTION RANGE*



*Actual range may vary depending on camera setup, environmental conditions, and user experience.







SCION OTM FEATURES

-  Rugged IP67-rated housing
-  Easy-to-use interface
-  Onboard video and image recording
-  White Hot, Black Hot, Iron Bow, Rainbow, Graded Fire, and Lava thermal palettes
-  Available in 640 x 512 (9 Hz) resolution
-  2x/4x/8x E-Zoom on 640 models

FLIR MD-Series™



MD-SERIES FEATURES

-  320 × 240 or 640 × 480 resolutions produce clear, detailed images
-  2x E-Zoom available on MD-324, 2x and 4x on MD-625
-  Automatic window heater keep optics free of ice
-  Ethernet-enabled for simple integration into your current electronics
-  Slim profile (7" high and only 1.36 kg/3 lbs) for an unobtrusive mount
-  Analog video output for easy connection to onboard monitors, recorders, or DVR systems



FIXED-MOUNT MARINE THERMAL VISION

This affordable, fixed-mount thermal night vision system helps you steer around obstacles, avoid collisions, and find people in the water, day or night. The MD camera body is simple to mount and easy to integrate into existing electronics. Mount the display separately on your helm, or view the video feed using existing multifunction navigation displays from leading manufacturers, including Furuno, Garmin, Raymarine, and Simrad.



Easily see navigation aids.

MD-SERIES THERMAL DETECTION RANGES*










*Actual range may vary depending on camera set-up, environmental conditions, and user experience.

FLIR M232 Series



M232 SERIES FEATURES

-  320 x 240 resolution for clear, detailed images
-  4x continuous E-Zoom magnifies distant targets for easy identification
-  Ethernet-enabled for simple integration with your other electronics
-  360° pan and +/-90° tilt capability
-  Rugged, waterproof gimbal enclosure with automatic window heaters for ice management
-  IP video for integration with latest state-of-the-art navigation displays (check FLIR.com for a list of compatible displays)
-  ClearCruise™ Obstacle Detection when connected to Raymarine Axiom systems

COMPACT MARINE THERMAL VISION

The M232 marine thermal camera takes affordability and easy integration to a whole new level. Incorporating 320 x 240 thermal resolution, video over IP, and digital zoom, M232 the smallest FLIR PTZ marine camera housing.



Available ClearCruise™ object detection technology alerts you to non-water obstacles and hazards.

IR ANALYTICS FOR ENHANCED AWARENESS


Combine the M232 with a Raymarine Axiom MFD and take advantage of FLIR ClearCruise™ object detection. ClearCruise provides audible and visible alerts to non-water objects such as boats, obstacles, or navigation markers in the scene.



M232 THERMAL DETECTION RANGES*



*Actual range may vary depending on camera setup, environmental conditions, and user experience.









REMOTE CONTROL

Control the M232 from your MFD or add the optional JCU-3 control unit.

FLIR M300 Series



M300 SERIES MARINE CAMERAS

-  Latest generation FLIR Boson™ sensor provides thermal vision in complete darkness, glare, and light fog
-  Two-axis mechanical stabilization virtually eliminates the effects of pitch, heave, and yaw
-  FLIR Color Thermal Vision™ and MSX® visible and thermal image blending technology for enhanced awareness
-  Available low light HD visible imaging sensor with long-range zoom offers enhanced target identification
-  FLIR ClearCruise™ object detection technology alerts you to non-water obstacles on both thermal and visible cameras
- IP** IP video, HD-SDI, and analog video outputs and integration with navigation displays
-  360° pan and +/-90° tilt capability




THE NEW STANDARD

The M300 Series sets a new standard for safe marine navigation and situational awareness. Applying marine video analytic technology to high-performance visible, thermal, or multispectral imaging, M300 Series marine cameras deliver unwavering vision in high-stakes environments.



Clearly identify navigation aids with Color Thermal Vision.



Control and view M300 Series direct from your MFD. The M300 Series integrates seamlessly with existing electronics, including select multifunction displays from Furuno, Garmin, Raymarine, and Simrad. An optional joystick control unit offers more precise control of M300 Series cameras.



GYRO-STABILIZATION

M300 Series cameras feature active gyro-stabilization so the cameras always deliver steady images, even in rough seas.




FLIR M300 Series



LONG-RANGE VISION

The M300C, M364C, and M364C LR are equipped with a high definition visible camera with 30x optical zoom and gyro-stabilization for exceptional long-range target identification.



M300-SERIES THERMAL DETECTION RANGES*



*Actual range may vary depending on camera setup, environmental conditions, and user experience.

FLIR M300C

HIGH-PERFORMANCE, LOW LIGHT MARINE VISIBLE CAMERA

The M300C's advanced near-infrared sensor gives you the power to see color even after dark. Able to use only ambient light to enhance your awareness and give you a clear picture, it's ideally suited for navigating intercoastal waterways at night. Combining a high-performance visible marine camera with outstanding optical zoom capabilities, the M300C provides positive target identification for law enforcement, commercial, and recreational boaters looking to monitor targets over long distances.



EXCEPTIONAL DAY & NIGHT VISION

- See in color even at night with near-infrared low light mode
- Locate and identify distant targets with 30x optical zoom
- Intelligent non-water object detection with Marine Video Analytics (MVA)



A STEADY VIEW IN ROUGH SEAS

- Two-axis stabilization virtually eliminates the effects of pitch, heave, and yaw
- Integrated AHRS (Attitude Heading Reference Sensor) delivers superior stabilization



MFD READY

- The M300C easily integrates with multifunction chartplotter displays from Raymarine, Furuno, Garmin, and Simrad/B&G
- ONVIF compliant for streamlined integration with a wide variety of video management systems

FLIR COLOR THERMAL VISION™ AND MSX®

While thermal cameras give mariners superior awareness on the water, thermal imaging alone does not capture important color information from other vessels or navigation aids. The dual sensor M364C and M364C LR offer mariners a new level of awareness via patented FLIR Color Thermal Vision (CTV) technology. This proprietary multispectral imaging technology for the FLIR M300 Series blends thermal and high definition visible color video for enhanced identification of buoys, vessels, and other targets at night. Additionally, the M364C and M364C LR models feature exclusive FLIR MSX® imaging technology, which blends edges and borders from the HD visible camera with the thermal image, giving operators improved visual recognition of distant objects.



Cameras can be installed ball down if required



Color Thermal Vision brings enhanced awareness at night of surrounding traffic with true color navigation lights, deck lighting, and much more.



Color Thermal Vision provides easy identification of illuminated navigation aids, such as lighthouses, daymarkers, and floating aids.




Exclusive FLIR Multi-spectral Dynamic Imaging (MSX) technology enhances thermal images with edges, patterns, text, and other high-contrast elements not always visible to the thermal camera alone.



Color Thermal Vision helps provide positive identification of fixed and floating navigation aids when running, day or night.



M300-SERIES THERMAL DETECTION RANGES*











*Actual range may vary depending on camera setup, environmental conditions, and user experience.

FLIR M400/M400XR




M400 AND M400XR FEATURES

-  High-intensity LED spot-beam can highlight targets of interest while preserving the night vision of on-deck personnel
-  HD color low light camera with 30x optical zoom
-  Gyro-stabilized to ensure steady viewing in heavy sea conditions
-  High-resolution 640 x 480 thermal sensor with 4x continuous optical zoom and 4x digital E-Zoom
-  Rugged, waterproof gimbal enclosure with automatic window heaters for ice management
-  360° pan and +/-90° tilt capability
- IP** IP video, HD-SDI, and analog video outputs and integration with navigation displays
-  Video tracking follows objects in the camera's view (M400XR only)
-  Firefighting mode optimizes color palette to see hot spots and measure temperature on-scene (M400XR only)

MULTI-SENSOR MARINE CAMERA SYSTEM

THERMAL CAMERA WITH CONTINUOUS OPTICAL ZOOM


The M400 thermal camera features a 4x optical zoom lens, plus an additional 4x digital zoom. See beyond visual range to identify distant contacts, or magnify small objects for easy identification. With continuous optical zoom, targets remain in clear, crisp focus right up to maximum magnification. Use the digital zoom to further expand the thermal image, making maximum usage of even the smallest pixels.



The optical zoom on the M400 helps positively identify distant targets



M400/M400XR THERMAL DETECTION RANGES*



*Actual range may vary depending on camera setup, environmental conditions, and user experience.

FLIR M400/M400XR



FLOATING ICE DETECTION AND AVOIDANCE

Nighttime collisions with sea ice are a legitimate hazard to expedition yachts, commercial vessels, and rescue craft operating in high latitudes and wintry conditions. FLIR systems with IceAlert™ mode can enhance situational awareness by highlighting growlers, bergy bits, and icebergs in shades of blue.



Ice detection mode



MULTI-SENSOR MARINE CAMERA SYSTEM

HD ZOOM VIDEO CAMERA

Better than binoculars, M400 is equipped with a built-in colour high definition camera with optical zoom and low light imaging. Use the video camera to make positive identification of other vessels, navigation aids, and more. Use its 30x optical zoom to see all the details and assess situations from a safe distance. Video and thermal zoom controls can be linked for easy comparison or simultaneous viewing.




M400XR VIDEO TRACKING

Video tracking keeps the M400XR locked on any target using the visible or thermal cameras. Once engaged, the system will pan and tilt the camera automatically to keep that target in view.



The M400 HD camera features a 30x optical zoom and gyro-stabilization. This ferry is well over 1 nautical mile away.




Video tracking

FLIR M400/M400XR



ADVANCED INTEGRATION


The M400 and M400XR offer multiple integration options. View and control them from leading marine MFDs from Furuno, Garmin, and Raymarine. The supplied JCU-2 joystick also offers primary control and access to all the M400 features. IP video allows the camera to network with onboard video surveillance systems, and HD-SDI output provides broadcast quality video to compatible displays. Analog output is also available for most marine displays and monitors. NMEA 0183 integration allows the M400/M400XR to slew to radar cursor locations, ARPA targets, or the active waypoint location.






MARINE FIREFIGHTING MODE (M400XR MODEL ONLY)

The M400XR adds a marine firefighting mode engineered for fireboats and rescue craft. Survey the scene and immediately see hot spots with a firefighting-specific isothermic color palette. M400XR instantly shows you temperatures on-screen to help you visualize your plan of attack, locate hot spots, and save lives and property. M400XR sees through smoke, steam, and darkness and identifies targets in scenes with extreme temperature dynamics.



Your Vision



Thermal Vision



HD Visible Camera and Spotlight



INTEGRATED LED SPOTLIGHT








Use the integrated spotlight on M400 to point out targets of interest, confirm navigational aids, light up the rescue zone, or just signal *I see you*. The narrow-beam LED spotlight is precisely aligned with the thermal and video camera payloads, making it easy to illuminate any target without embarrassing other vessels or spoiling the night vision of on-deck crew.

FLIR M500™



FLIR

M500 FEATURES

-  Cooled MWIR Thermal imager with 640 × 512 resolution and 14x Optical Zoom
-  High-intensity LED spot-beam can highlight targets of interest while preserving the night vision of on-deck personnel
-  HD color low light camera with 30x optical zoom
-  Gyro-stabilized to ensure steady viewing in heavy sea conditions
-  Rugged, waterproof gimbal enclosure with automatic window heaters for ice management
-  360° pan and +/-90° tilt capability
-  Video tracking follows objects in the camera's view
- IP** IP video, HD-SDI, and analog video outputs and integration with navigation displays

M500 ULTRA HIGH-PERFORMANCE MULTI-SENSOR CAMERA SYSTEM

CRYOGENICALLY COOLED FOR EXTREME LONG-RANGE DETECTION

A liquid helium cooling system in the M500 chills its internal sensor to a frigid -387°F (-233°C), making it super-sensitive, even at long range. M500 can detect a man-sized target at ranges approaching five nautical miles and small vessels at over eight nautical miles. M500 lets you detect vessels and classify onboard activities at extreme standoff ranges.



The M500 thermal camera has a 14x optical zoom, 4x E-Zoom, and gyro-stabilization for superior long-range detection. The small boat pictured here is over two nautical miles away.

THERMAL VISION WITH CONTINUOUS OPTICAL ZOOM



The M500 thermal camera core features a 14x optical zoom lens plus an additional 4x digital zoom. See well beyond visual range to identify distant contacts or magnify small objects for easy identification. With continuous optical zoom, targets remain in clear, crisp focus right up to maximum magnification. Use the digital zoom to further expand the thermal image, making maximum usage of even the smallest pixels.

FLIR M500



ADVANCED RADAR INTEGRATION

Link the M400, M400XR, and M500 with your NMEA0183-compatible radar and enjoy an even higher level of integration. The M500 pan and tilt gimbal can receive coordinates from the radar system and slew to them automatically. Quickly identify tracked ARPA targets. Place the radar cursor on an unknown target and let the M500 show you what's there. M500 can even auto-slew to show you visually the bearing to your next GPS waypoint.



Advanced radar integration with M500 enables the camera auto-slew between multiple tracked ARPA targets.



SUPERIOR ALL-WEATHER THERMAL IMAGING

The M500 cooled thermal sensor has twice the sensitivity of uncooled systems. This gives enhanced contrast, clarity, and detail in every image. Plus, M500 sees in the mid-wave infrared (MWIR) spectrum. Light fog, smoke, haze, and offshore marine layer are nearly invisible in this spectral range.



VIDEO TRACKING

Video tracking keeps the M500 locked on any target using the visible or thermal cameras. Once engaged, the system will pan and tilt the camera automatically to keep that target in view.

Select any in-view object of interest with the joystick controller to enable video tracking.

FLIR M500



INTEGRATED LED SPOTLIGHT

Use the integrated spotlight on the M400, M400XR, and M500 to point out targets of interest, confirm navigational aids, light up the rescue zone, or just signal *I see you*. The narrow-beam LED spotlight is precisely aligned with the thermal and video camera payloads, making it easy to illuminate any target without embarrassing other vessels or spoiling the night vision of on-deck crew.



M500 THERMAL DETECTION RANGES*



M500





HD ZOOM VIDEO CAMERA


A low light, high definition visible imaging camera on the M400, M400XR, and M500 helps identify other vessels and navigation aids better than conventional binoculars. With a 30x optical zoom lens and active stabilization, the HD zoom video camera captures key details and distant activity for safer decisions on the water. Visible and thermal camera controls can link for easy comparison and side-by-side viewing.



Integrated LED spotlight.



High-sensitivity mid-wave detector offers the best image quality and long-range object recognition.



M500 allows you to observe human activity at extremely long ranges.

Human: 2.0nm (3625m)

Boat: 5.0nm (9260m)

*Actual range may vary depending on camera setup, environmental conditions, and user experience.


THERMAL CAMERA FEATURES COMPARISON CHART

| |
|--|
| Feature: |
| Thermal Night Vision: Day or night operation without any ambient light. |
| Digital Thermal Zoom: Thermal image is magnified by pixel stretching, making small or distant targets appear larger for easier viewing. |
| Color Thermal Vision and MSX™. Enhanced blending brings true color to thermal night vision images, or enhanced edge detail. |
| Analog Video Output: Connect the camera to monitors, televisions, and marine displays with standard composite analog video. |
| Gyro-stabilized: Sensors in the camera's gimbal system detect and counteract vessel motion for smooth viewing in rough seas. |
| Horizontal Stabilization: The camera can hold on a selected azimuth or bearing, regardless of vessel heading changes, to maintain visibility of a scene. |
| Multifunction Display Integration: Controllable from major brands of marine MFD's, such as Raymarine, Garmin, Furuno, and Simrad. |
| Video Over IP Output: Streams network video over standard Ethernet networks to computers and compatible marine MFDs. |
| MFD Slew to Cue: The thermal camera can respond to cues from a networked marine multifunction display. Cues include dangerous ARPA or AIS contact alarms, the GPS position of a man overboard alarm, or locking onto a point designated from the electronic chart. |
| Pan and Tilt Control: Slew the camera +/- 360° horizontally and +/- 90° vertically for horizon-to-horizon viewing of targets. |
| HD Color Zoom Camera: Augments the thermal imager with color and low light video for positive target verification and enhanced surveillance. |
| Optical Thermal Zoom: Advanced lens system magnifies small objects or distant targets for easy identification. Targets remain in clear, sharp focus at maximum optical magnification. |
| Video Tracker: Lock the camera on a suspect, victim, or incident scene. The camera's pan and tilt system will automatically keep that object in-frame. |
| NMEA 0183 Integration: Send coordinates from your radar system to the camera's pan and tilt drive to keep selected radar targets in view, follow the radar cursor, or see upcoming GPS waypoints. |
| Thermal Vessel Detection: What is the typical range at which this camera can detect a small vessel using thermal? |



| Scion Handhelds | MD-Series | M232 | M300C | M332, M364 | M364C, M364C LR | M400 | M400XR | M500 |
|-----------------|---------------|--------|-------|---------------|-----------------|--------|--------|---------|
| • | • | • | | • | • | • | • | • |
| • | • | • | | • | • | • | • | • |
| | | | | | • | • | | |
| | • | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | • | • | • | • | • | • | • | • |
| | | • | • | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| | | | | • | • | • | • | • |
| .48 - 1.7 nm | 1.0 to 1.7 nm | 1.0 nm | N/A | 1.0 to 1.7 nm | 1.7 to 2.0 nm | 3.7 nm | 3.7 nm | 5.0 nm |
| 0.9 - 3.2 km | 1.8 to 3.1 km | 1.8 km | N/A | 1.8 to 3.1 km | 3.1 to 3.7 km | 6.8 km | 6.8 km | 9.26 km |

SCION HANDHELD SPECIFICATIONS



WHAT'S IN THE BOX:


EVERY SCION OTM THERMAL HANDHELD MONOCULAR INCLUDES:

- USB charging cable with universal AC adapter
- Custom video-out cable
- Wrist strap
- Molle bag
- Quick start guide

SCION OTM260

| MAIN THERMAL CAMERA | |
|--------------------------------|---|
| Core Technology | BOSON 12 μ m VOx Microbolometer |
| Detector Resolution | 640 \times 512 |
| Lens System | 18 mm |
| Field of View (H \times W) | 24° \times 18° |
| Optical Magnification | 1x |
| Digital Zoom | 1X 2X 4X 8X |
| Refresh Rate | 9 Hz |
| Video Recording | Yes |
| Image Capturing | Yes |
| Internal Memory | 2 GB Internal Storage / Optional microSD™ Card (up to 128 GB) |
| Focusing Range | ∞ |
| Eye Relief | 16 mm |
| Display | Quad-VGA (1280 \times 960) High definition display |
| Display Focus | Manual |
| INTERFACING | |
| USB Type | USB-C; Power In; Video Out; Video and Image File Transfer |
| POWER | |
| Battery Life | Up to 4.5 hours at 20°C |
| Battery Type | 6x CR123A 3V Lithium Battery |
| COMMUNICATIONS | |
| NFC (Near-Field Communication) | Yes |
| Bluetooth™ | BLE 4.1+ |
| Wi-Fi | Video Streaming |
| GPS | No |
| PHYSICAL | |
| Weight | Without Batteries: 452 g; With Batteries 572 g |
| Size | 227 \times 76.8 \times 60.5 mm (9 \times 3 \times 2.4 in) |
| Color (Housing) | Gray / Black |
| Mounting | ¼-20 Tripod Mount |

MD-SERIES SPECIFICATIONS




WHAT'S IN THE BOX:

EVERY MD-SERIES THERMAL CAMERA SYSTEM INCLUDES:

- Camera unit
- Camera base O-ring
- RJ-45 Ethernet cable, double shielded, low smoke zero halogen (LSZH) rated, 25 feet (7.7 meters)
- Coaxial video output cable, 25 feet (7.7 meters)
- 12V DC Power Over Ethernet (PoE) injector
- RJ45 weatherproof coupler
- Female-to-female F-type video connectors
- Stainless steel mounting hardware kit


| | MD-324 | MD-625 | | |
|---------------------------------|---|------------------------------|---------------|-----------|
| MAIN THERMAL CAMERA | | | | |
| Field of View | 24° × 18° (NTSC) | 25° × 20° (NTSC) | | |
| Video Refresh Rate | <9 Hz or 30 Hz (NTSC and PAL) | | | |
| Focal Length | 19 mm | 25 mm | | |
| Focus | Fixed 12ft (3.6m) to infinity | | | |
| Optical Zoom | N/A | | | |
| Digital Zoom | 2x | 2x, 4x | | |
| Detector Type | 320 × 240 VOx Microbolometer | 640 × 480 VOx Microbolometer | | |
| SYSTEM SPECIFICATIONS | | | | |
| Gyro Stabilized | No | | | |
| Video Tracking | No | | | |
| Firefighter Mode | No | | | |
| Pan/Tilt Adjustment Range | Pan: ±30° per key, Tilt: +34°, -27° (Locked in at Installation) | | | |
| Analog Video Output | NTSC or PAL, 30 Hz or <9 Hz | | | |
| Analog Video Connector Types | F-type BNC with BNC-to-RCA adapter included for video out | | | |
| Network Video Output | No | | | |
| HD-SDI Lossless Video Output | No | | | |
| Power Requirements | PoE injector required per IEEE 802.3af, 12-24 V DC | | | |
| Power Consumption | 4.8 W nominal; 12.5 W max | | | |
| ENVIRONMENTAL | | | | |
| Operating Temperature Range | -13°F to +131°F (-25°C to +55°C) | | | |
| Storage Temperature Range | -40°F to +185°F (-40°C to +85°C) | | | |
| Automatic Window Defrost | Standard at Power-Up | | | |
| Sand/Dust Ingress | Mil-Std-810E | | | |
| Water Ingress | IPX 6 (heavy seas, powerful jets of water) | | | |
| Shock | 15 g vertical, 9 g horizontal | | | |
| Vibration | IEC 60945; MIL-STD-810E | | | |
| Lightning Protection | Standard | | | |
| Salt Mist | IEC60945 | | | |
| Wind | 100 knot (115.2 mph) | | | |
| EMI | IEC 60945 | | | |
| PHYSICAL | | | | |
| Weight | ~ 3 lbs (1.36 kg) | | | |
| Size | 6" (152.4 mm) dia. × 7" (177.8 mm) ht. | | | |
| RANGE PERFORMANCE | | | | |
| Clear Weather Range Performance | metres | nm | metres | nm |
| Detect a 30-foot Vessel | 1850.0 | 1.0 | 3150.0 | 1.7 |
| NATO Target 2.3m x 2.3m @50% | 1285.0 | 0.7 | 1691.0 | 0.9 |
| Detect Human-Sized Target | 560.0 | 0.3 | 735.0 | 0.4 |

M232 SPECIFICATIONS



WHAT'S IN THE BOX: EVERY M232 THERMAL CAMERA INCLUDES:


- Camera unit
- Top-down riser kit
- Thermal camera base-seal
- Right-angled RayNet to RayNet cable, 32 feet (10 meters)
- RayNet to RJ45 adapter cable, 4-inches (100mm)
- Right-angled 3-pin power cable, 32 feet (10 meters)
- Stainless steel mounting hardware kit



Thermal camera shown with optional riser

| | M232 | |
|---------------------------------|---|-----------|
| MAIN THERMAL CAMERA | | |
| Field of View | 24° × 18° | |
| Video Refresh Rate | 9 Hz | |
| Focal Length | 19mm | |
| Focus | Fixed 12ft (3.6m) to infinity | |
| Optical Zoom | N/A | |
| Digital Zoom | 4x Continuous | |
| Detector Type | 320 × 240 VOx Microbolometer | |
| SYSTEM SPECIFICATIONS | | |
| Gyro Stabilized | No | |
| ClearCruise Analytics | Yes, with Raymarine Axiom | |
| Video Tracking | No | |
| Firefighter Mode | No | |
| Pan/Tilt Adjustment Range | Pan: 360° (continuous), Tilt: +110°, -90° | |
| Analog Video Output | No | |
| Analog Video Connector Types | N/A | |
| Network Video Output | Single H.264 Network Video Stream | |
| HD-SDI Lossless Video Output | No | |
| Power Requirements | 12 or 24 VDC | |
| Power Consumption | 15 W (typical) 18 W (max) | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -13°F to +131°F (-25°C to +55°C) | |
| Storage Temperature Range | -30°F to +158°F (-30°C to +70°C) | |
| Automatic Window Defrost | Standard at Power-Up | |
| Sand/Dust Ingress | Mil-Std-810E | |
| Water Ingress | IPX 6 (heavy seas, powerful jets of water) | |
| Shock | 15 g vertical, 9 g horizontal | |
| Vibration | IEC 60945; MIL-STD-810E | |
| Lightning Protection | Standard | |
| Salt Mist | IEC60945 | |
| Wind | 100 knot (115.2 mph) | |
| EMI | IEC 60945 | |
| PHYSICAL | | |
| Weight | 6.0 lb (2.7 kg) w/o top-down riser 6.6 lb (3.0 kg) w/ top-down riser | |
| Size | 6.34" (dia. @ base) x 9.03" (ht.) 161.1 (dia.) x 229.3 (ht.) mm | |
| RANGE PERFORMANCE | | |
| Clear Weather Range Performance | metres | nm |
| Detect a 30-foot Vessel | 1850.0 | 1.0 |
| NATO Target 2.3m x 2.3m @50% | 1285.0 | 0.7 |
| Detect Human-Sized Target | 560.0 | 0.3 |

M300 SERIES SPECIFICATIONS




WHAT'S IN THE BOX: EVERY M300 CAMERA SYSTEM INCLUDES:

- Camera unit
- Camera base-seal
- Camera gasket
- RayNet-to-RJ45 adaptor cable 120 mm (4.72 in.)
- Right-angled RayNet-to-RayNet cable 3 m (9.8 ft.)
- Right-angled BNC-to-BNC cable 3 m (9.8 ft.)
- Right-angled 3-pin power cable 3 m (9.8 ft.)
- Mounting riser
- 3 x camera fixings: nuts, dome nuts, spring and flat washers, threaded studs
- 2 x self-adhesive decals (for ball-down mounting only)
- Documentation pack

| | M300C | M332 | |
|---------------------------------|---|---|-----------|
| MAIN THERMAL CAMERA | | | |
| Video Refresh Rate | N/A | 30 Hz or <9 Hz | |
| Field of View | N/A | 24 ° x 18 ° | |
| Focal Length | N/A | 9.1mm | |
| Focus | N/A | Fixed 12 ft (3m) to infinity | |
| Optical Zoom | N/A | N/A | |
| E-Zoom | N/A | 4x Continuous | |
| Image Processing | N/A | FLIR Proprietary Digital Detail Enhancement | |
| Detector Type | N/A | 320 x 256 VOx Microbolometer | |
| MAIN VISIBLE CAMERA | | | |
| Detector Type | 1/2.8" Exmor R CMOS | N/A | |
| Resolution | High Definition up to 1080/30p | N/A | |
| Minimum Illumination | 0.1 lux (50 IRE, 1/30s, ICR off, slow shutter off, high sensitivity off) / 0.0008 lux (30 IRE, ICR on, slow shutter 1/4s, high sensitivity on) | N/A | |
| Zoom | 30x Optical Zoom | N/A | |
| E-Zoom | 12x | N/A | |
| Focal Length | 129 mm to 4.3 mm | N/A | |
| Field of View | Optical 63.7° x 35.8° WFOV to 2.3° x 1.29° NFOV | N/A | |
| SYSTEM SPECIFICATIONS | | | |
| Gyro Stabilized | | | |
| ClearCruise Analytics | | | |
| Color Thermal Vision (CTV) | | No | |
| Multispectral Imaging (MSX) | | No | |
| Video Tracking | | | |
| Firefighter Mode | | | |
| Pan/Tilt Adjustment Range | | | |
| Analog Video Output | | | |
| Analog Video Connector Types | | | |
| Network Video Output | | | |
| HD-SDI Lossless Video Output | | | |
| Power Requirements | | | |
| Power Consumption | | | |
| ENVIRONMENTAL | | | |
| Operating Temperature Range | -13°F to +131°F (-25°C to +55°C) | -13°F to +131°F (-25°C to +55°C) | |
| Storage Temperature Range | -30°F to +158°F (-30°C to +70°C) | -30°F to +158°F (-30°C to +70°C) | |
| Automatic Window Defrost | Standard at Power-Up | Standard at Power-Up | |
| Sand/Dust Ingress | Mil-Std-810E or IP6X | Mil-Std-810E or IP6X | |
| Water Ingress | IPX6 (heavy seas, power jets of water) | IPX6 (heavy seas, power jets of water) | |
| Shock | 15g vertical, 9g horizontal | 15g vertical, 9g horizontal | |
| Vibration | IEC60945 | IEC60945 | |
| Lightning Protection | Standard | Standard | |
| Salt Mist | IEC60945 | IEC60945 | |
| Wind | 100 knots (115.2 MPH) | 100 knots (115.2 MPH) | |
| EMI | IEC60945 | IEC60945 | |
| PHYSICAL | | | |
| Weight | 12.9 lbs (5.9 kg) / Camera with top-down riser: 13.9 lbs (6.3 kg) | 12.9 lbs (5.9 kg) / Camera with top-down riser: 13.9 lbs (6.3 kg) | |
| Size | Camera: Base diameter: 222.2 mm (8.7 in.) Height: 328.3 mm (12.9 in.) Camera attached to mounting riser: Base diameter (with seal): 254.0 mm (10.0 in.) Height: 365.5 mm (14.4 in.) | Camera: Base diameter: 222.2 mm (8.7 in.) Height: 328.3 mm (12.9 in.) Camera attached to mounting riser: Base diameter (with seal): 254.0 mm (10.0 in.) Height: 365.5 mm (14.4 in.) | |
| RANGE PERFORMANCE | | | |
| Clear Weather Range Performance | | metres | nm |
| Detect a 30-foot Vessel | N/A | 1850.0 | 1.0 |
| NATO Target 2.3m x 2.3m @50% | N/A | 1285.0 | 0.7 |
| Detect Human-Sized Target | N/A | 560.0 | 0.3 |


| M364 | | M364C | | M364C LR | |
|---|--|---|--|---|--|
| | | 30 Hz or <9 Hz | | | |
| 24 ° x 18 ° | | 24 ° x 18 ° | | 18 ° x 13.5 ° | |
| 18 mm | | 18 mm | | 25 mm | |
| Fixed 12 ft (3m) to infinity | | Fixed 12 ft (3m) to infinity | | Fixed 12 ft (3m) to infinity | |
| N/A | | N/A | | N/A | |
| 8x Continuous | | 8x Continuous | | 8x Continuous | |
| FLIR Proprietary Digital Detail Enhancement | | FLIR Proprietary Digital Detail Enhancement | | FLIR Proprietary Digital Detail Enhancement | |
| 640 x 512 VOx Microbolometer | | 640 x 512 VOx Microbolometer | | 640 x 512 VOx Microbolometer | |
| N/A | | 1/2.8" Exmor R CMOS | | 1/2.8" Exmor R CMOS | |
| N/A | | High Definition up to 1080/30p | | High Definition up to 1080/30p | |
| N/A | | 0.1 lux (50 IRE, 1/30s, ICR off, slow shutter off, high sensitivity off) / 0.0008 lux (30 IRE, ICR on, slow shutter 1/4s, high sensitivity on) | | 0.1 lux (50 IRE, 1/30s, ICR off, slow shutter off, high sensitivity off) / 0.0008 lux (30 IRE, ICR on, slow shutter 1/4s, high sensitivity on) | |
| N/A | | 30x Optical Zoom | | 30x Optical Zoom | |
| N/A | | 12x | | 12x | |
| N/A | | 129 mm to 4.3 mm | | | |
| N/A | | Optical 63.7° x 35.8° WFOV to 2.3° x 1.29° NFOV | | | |
| Yes | | | | | |
| Yes | | | | Yes | |
| | | | | Yes | |
| No | | | | | |
| No | | | | | |
| 360° Continuous Pan, +/- 90° Tilt | | | | | |
| NTSC/PAL User Settable | | | | | |
| BNC | | | | | |
| Single H.264 Network Video Stream | | | | | |
| Yes | | | | | |
| 12 to 24vDC (24vDC recommended) | | | | | |
| 41 W typical, 56 W typical (with heaters on.) Note: FLIR recommends using a 75 W power supply | | | | | |
| | | | | | |
| -13°F to +131°F (-25°C to +55°C) | | -13°F to +131°F (-25°C to +55°C) | | -13°F to +131°F (-25°C to +55°C) | |
| -30°F to +158°F (-30°C to +70°C) | | -30°F to +158°F (-30°C to +70°C) | | -30°F to +158°F (-30°C to +70°C) | |
| Standard at Power-Up | | Standard at Power-Up | | Standard at Power-Up | |
| Mil-Std-810E or IP6X | | Mil-Std-810E or IP6X | | Mil-Std-810E or IP6X | |
| IPX6 (heavy seas, power jets of water) | | IPX6 (heavy seas, power jets of water) | | IPX6 (heavy seas, power jets of water) | |
| 15g vertical, 9g horizontal | | 15g vertical, 9g horizontal | | 15g vertical, 9g horizontal | |
| IEC60945 | | IEC60945 | | IEC60945 | |
| Standard | | Standard | | Standard | |
| IEC60945 | | IEC60945 | | IEC60945 | |
| 100 knots (115.2 MPH) | | 100 knots (115.2 MPH) | | 100 knots (115.2 MPH) | |
| IEC60945 | | IEC60945 | | IEC60945 | |
| 12.9 lbs (5.9 kg) / Camera with top-down riser: 13.9 lbs (6.3 kg) | | 6.3 kg (13.9 lb) without mounting riser; 6.75 kg (14.9 lb) with mounting riser. | | 6.3 kg (13.9 lb) without mounting riser; 6.75 kg (14.9 lb) with mounting riser. | |
| Camera: Base diameter: 222.2 mm (8.7 in.) Height: 328.3 mm (12.9 in.) Camera attached to mounting riser: Base diameter (with seal): 254.0 mm (10.0 in.) Height: 365.5 mm (14.4 in.) | | Camera: Base diameter: 222.2 mm (8.7 in.) Height: 328.3 mm (12.9 in.) Camera attached to mounting riser: Base diameter (with seal): 254.0 mm (10.0 in.) Height: 365.5 mm (14.4 in.) | | Camera: Base diameter: 222.2 mm (8.7 in.) Height: 328.3 mm (12.9 in.) Camera attached to mounting riser: Base diameter (with seal): 254.0 mm (10.0 in.) Height: 365.5 mm (14.4 in.) | |
| metres | | nm | | metres | |
| 3150.0 | | 1.7 | | 3700.0 | |
| 1691.0 | | 0.9 | | 2368.0 | |
| 925.0 | | 0.5 | | 1030.0 | |
| metres | | nm | | metres | |
| 3150.0 | | 1.7 | | 3700.0 | |
| 1691.0 | | 0.9 | | 2368.0 | |
| 925.0 | | 0.5 | | 1030.0 | |

M400 SPECIFICATIONS



WHAT'S IN THE BOX: EVERY M400 AND M400XR THERMAL CAMERA SYSTEM INCLUDES:


- Camera unit
- FLIR Joystick Control Unit (JCU2) kit
- 5-Port PoE+ Ethernet Switch
- Power cable, right angle, 12 AWG, 3 meters
- Ethernet cable, right angle to RJ45, 1 meter
- RJ45 waterproof Ethernet coupler
- AV and serial cable, right angle, 1 meter
- HD-SDI cable, 1 meter
- HD-SDI Isolation Transformer
- Camera base O-ring and stainless steel mounting hardware kit



Thermal camera shown with optional riser

| | M400 | M400XR | | |
|---------------------------------|---|---|---------------|-----------|
| MAIN THERMAL CAMERA | | | | |
| Field of View | 24° to 6° HFOV / 1.5° HFOV with e-zoom | 24° to 6° HFOV / 1.5° HFOV with e-zoom | | |
| Video Refresh Rate | <9 Hz or 30 Hz (NTSC and PAL) | <9 Hz or 30 Hz (NTSC and PAL) | | |
| Focal Length | 26 mm (Wide) to 105 mm (Narrow) | 26 mm (Wide) to 105 mm (Narrow) | | |
| Focus | Controlled by JCU | Controlled by JCU | | |
| Optical Zoom | 4x | 4x | | |
| Digital Zoom | 4x Continuous | 4x Continuous | | |
| Detector Type | 640 x 512 VOx Microbolometer | 640 x 512 VOx Microbolometer | | |
| MAIN VISIBLE CAMERA | | | | |
| Detector Type | 1/2.8" CMOS | 1/2.8" CMOS | | |
| Lines of Resolution | 1920 x 1080 | 1920 x 1080 | | |
| Minimum Illumination | 0.35 lux at F1.6, AGC On, 1/30s High Sensitivity Mode / 1.4 lux Normal Mode | | | |
| Zoom | 30x Optical Zoom | 30x Optical Zoom | | |
| E-Zoom | 12x (360x total digital and optical zoom) | 12x (360x total digital and optical zoom) | | |
| Focal Length | 129 mm to 4.3 mm | 129 mm to 4.3 mm | | |
| Field of View | Optical 63.7° x 35.8° WFOV to 2.3° x 1.29° NFOV | Optical 63.7° x 35.8° WFOV to 2.3° x 1.29° NFOV | | |
| SPOTLIGHT SPECIFICATIONS | | | | |
| Type, Lumens, Beam° | LED, 580 Lumens, 5° Divergence Angle | LED, 580 Lumens, 5° Divergence Angle | | |
| SYSTEM SPECIFICATIONS | | | | |
| Gyro Stabilized | Yes | Yes | | |
| Video Tracking | No | Yes | | |
| Firefighter Mode | No | Yes | | |
| Pan/Tilt Adjustment Range | 360° Continuous Pan, ± 90° Tilt | 360° Continuous Pan, ± 90° Tilt | | |
| Analogue Video Output | NTSC or PAL, 30 Hz or <9 Hz | NTSC or PAL, 30 Hz or <9 Hz | | |
| Analogue Video Connector Types | F-type BNC with BNC-to-RCA adapter included for video out | F-type BNC with BNC-to-RCA adapter included for video out | | |
| Network Video Output | Dual, Independent H.264 Network Video Streams | Dual, Independent H.264 Network Video Streams | | |
| HD-SDI Lossless Video Output | Yes | Yes | | |
| Power Requirements | 12-24V DC | 12-24V DC | | |
| Power Consumption | <50 W nominal; 130 W peak, 270 W 2/heaters | <50 W nominal; 130 W peak, 270 W 2/heaters | | |
| ENVIRONMENTAL | | | | |
| Operating Temperature Range | -13°F to +131°F (-25°C to +55°C) | -13°F to +131°F (-25°C to +55°C) | | |
| Storage Temperature Range | -56° F to + 176°F (-50°C to +80°C) | -56° F to + 176°F (-50°C to +80°C) | | |
| Automatic Window Defrost | Standard at Power-Up | Standard at Power-Up | | |
| Sand/Dust Ingress | Mil-Std-810E | Mil-Std-810E | | |
| Water Ingress | IPX 6 (heavy seas, powerful jets of water) | IPX 6 (heavy seas, powerful jets of water) | | |
| Shock | 15 g vertical, 9 g horizontal | 15 g vertical, 9 g horizontal | | |
| Vibration | IEC 60945; MIL-STD-810E | IEC 60945; MIL-STD-810E | | |
| Lightning Protection | Standard | Standard | | |
| Salt Mist | IEC60945 | IEC60945 | | |
| Wind | 100 knot (115.2 mph) | 100 knot (115.2 mph) | | |
| EMI | IEC 60945 | IEC 60945 | | |
| PHYSICAL | | | | |
| Weight | 28 lbs (12.7 kg) | 28 lbs (12.7 kg) | | |
| Size | 10.75" (273.1 mm) x 15.65" (397.6 mm) – 18.05" (458.7mm) high with top down riser | | | |
| RANGE PERFORMANCE | | | | |
| Clear Weather Range Performance | metres | nm | metres | nm |
| Detect a 30-foot Vessel | 6850.0 | 3.7 | 6850.0 | 3.7 |
| NATO Target 2.3m x 2.3m @50% | 4722.0 | 2.5 | 4722.0 | 2.5 |
| Detect Human-Sized Target | 1800.0 | 1.0 | 1800.0 | 1.0 |


M500 SPECIFICATIONS



WHAT'S IN THE BOX:

EVERY M500 THERMAL CAMERA SYSTEM INCLUDES:

- Camera unit
- FLIR Joystick Control Unit (JCU2) kit
- 5-Port PoE+ Ethernet Switch
- Power cable, right angle, 12 AWG, 3 meters
- Ethernet cable, right angle to RJ45, 1 meter
- RJ45 waterproof Ethernet coupler
- AV and serial cable, right angle, 1 meter
- HD-SDI cable, 1 meter
- HD-SDI Isolation Transformer
- Camera base O-ring and stainless steel mounting hardware kit



Thermal camera shown with optional riser

| M500 | | |
|---------------------------------|---|-----------|
| MAIN THERMAL CAMERA | | |
| Field of View | Optical 28° x 21° WFOV to 2° x 1.5° NFOV | |
| Video Refresh Rate | 25 Hz (PAL) / 30 Hz (NTSC) | |
| Focal Length | 19mm (Wide) to 275mm (Narrow) | |
| Focus | Controlled by JCU | |
| Optical Zoom | 1x to 14x (continuous) | |
| Digital Zoom | 4x Continuous | |
| Detector Type | Cooled MWIR InSb 640x512 Focal Plane Array | |
| MAIN VISIBLE CAMERA | | |
| Detector Type | 1/2.8" CMOS | |
| Lines of Resolution | 1920 x 1080 | |
| Minimum Illumination | 0.35 lux at F1.6, AGC On, 1/30s High Sensitivity Mode / 1.4 lux Normal Mode | |
| Zoom | 30x Optical Zoom | |
| E-Zoom | 12x (360x total digital and optical zoom) | |
| Focal Length | 129 mm to 4.3 mm | |
| Field of View | Optical 63.7° x 35.8° WFOV to 2.3° x 1.29° NFOV | |
| SPOTLIGHT SPECIFICATIONS | | |
| Type, Lumens, Beam° | LED, 580 Lumens, 5° Divergence Angle | |
| SYSTEM SPECIFICATIONS | | |
| Gyro Stabilized | Yes | |
| Video Tracking | Yes | |
| Firefighter Mode | No | |
| Pan/Tilt Adjustment Range | 360° Continuous Pan, ± 90° Tilt | |
| Analogue Video Output | NTSC or PAL, 30 Hz or <9 Hz | |
| Analogue Video Connector Types | F-type BNC with BNC-to-RCA adapter included for video out | |
| Network Video Output | Dual, Independent H.264 Network Video Streams | |
| HD-SDI Lossless Video Output | Yes | |
| Power Requirements | 12-24V DC | |
| Power Consumption | 250 W (max w/heaters) | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -13°F to +131°F (-25°C to +55°C) | |
| Storage Temperature Range | -56° F to + 176°F (-50°C to +80°C) | |
| Automatic Window Defrost | Standard at Power-Up | |
| Sand/Dust Ingress | Mil-Std-810E | |
| Water Ingress | IPX 6 (heavy seas, powerful jets of water) | |
| Shock | 15 g vertical, 9 g horizontal | |
| Vibration | IEC 60945; MIL-STD-810E | |
| Lightning Protection | Standard | |
| Salt Mist | IEC60945 | |
| Wind | 100 knot (115.2 mph) | |
| EMI | IEC 60945 | |
| PHYSICAL | | |
| Weight | 32 lb (14.5 kg) | |
| Size | 10.75" (273 mm) dia. x 15.65" (397.5 mm) ht | |
| RANGE PERFORMANCE | | |
| Clear Weather Range Performance | metres | nm |
| Detect a 30-foot Vessel | 9260.0 | 5.0 |
| NATO Target 2.3m x 2.3m @50% | 6482.0 | 3.5 |
| Detect Human-Sized Target | 3625.0 | 2.0 |

US EXPORT REGULATIONS

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved

WARRANTY

Select FLIR maritime cameras are backed by a 2-year standard warranty and our commitment to world-class service and support. By registering your system at flir.com/support, the 2-year standard limited warranty is upgraded to a 3-year extended limited warranty for free.

FLIR M500 cameras are backed by a 2-year/10,000 hour limited warranty.

Visit flir.com/marine for complete warranty details

FLIR SYSTEMS INC.
27700 SW PARKWAY AVE
WILSONVILLE, OR 97070
USA
503-498-3547

FLIR MARITIME US, INC.
9 TOWNSEND WEST
NASHUA, NH 03063
USA
603-324-7900

FLIR SYSTEMS BVBA
LUXEMBURGSTRAT 2, 2321
MEER
BELGIUM
+32 (0)3 287 87 10

19-2389-MAR - SEPTEMBER 2022

